

4/PRTS

0/031829  
531 Rec'd PCT/PT 22 JAN 2002

1 STATOR

2  
3 Related Art

4  
5 The invention is based on a stator according to the definition of the species in  
6 Claim 1.

7  
8 A stator has already been made known in US-PS 5,089,730, onto the stator pole  
9 teeth of which a preassembled coil is slid. The coils are secured to the stator pole  
10 teeth by means of a single part.

11  
12 This has the disadvantage, however, that a magnetic flux in the winding head of  
13 the exciting coil cannot be directed in defined fashion, and therefore does not  
14 contribute to the torque of the rotor, nor is there a gap in the foot of the tooth.

15  
16 Advantages of the Invention

17  
18 In contrast, the stator according to the invention having the characterizing  
19 features in Claim 1 has the advantage that a stator can be produced in simple  
20 fashion that makes smaller tolerances possible and has improved performance  
21 data, such as a higher slot fill factor of the excitation coils, less space required to  
22 install the motor, reduced stop torques, and higher torque, for example.

23  
24 Advantageous further developments and improvements of the stator named in  
25 Claim 1 are possible due to the measures listed in the dependent claims.

26  
27 It is advantageous that a pole shoe is made of magnetically soft solid material,  
28 because a magnetic stray flux of a winding head of an exciting coil can then be  
29 directed in all spacial directions in defined fashion and contribute to the magnetic  
30 excitation.

31

1 It is further advantageous that a coil insulating frame is located on the pole shoe,  
2 because a coil can then be wound in simple fashion.

3  
4 A coil can be electrically connected to an external power source or electrical  
5 control in advantageous fashion if an electrical connecting element is integrated  
6 in the coil insulating frame.

### 7 8 Brief Description of the Drawing

9  
10 Simplified versions of the exemplary embodiments of the invention are shown in  
11 the drawing and described in greater detail in the subsequent description.

12  
13 Figure 1 shows a first exemplary embodiment of a stator designed according to  
14 the invention,

15 Figure 2 shows a pole shoe,

16 Figure 3 shows an oblong pole shoe,

17 Figure 4 shows an oblong pole shoe having a coil frame.

### 18 19 Detailed Description of the Exemplary Embodiments

20  
21 Figure 1 shows a stator 1, according to the invention, of an electrical machine,  
22 such as an internal rotor motor, for example. The stator 1 is formed by a stator  
23 ring 3 that comprises at least one stator pole tooth 7 and a centerline 2. The  
24 stator ring 3 is made of a solid material, or it is laminated. The, e.g., six stator  
25 pole teeth 7 present, extending radially inward, are distributed evenly around the  
26 centerline 2.

27  
28 A coil 11 is slid onto each stator pole tooth 7. These are preassembled coils 11,  
29 for example, e.g., "stoved-enamel" coils, or they are coils 11 wound onto a coil  
30 frame 28. The coils 11 can also be compound coils.

1 Each coil 11 is secured to the stator pole tooth 7 by means of one pole shoe 15.  
2 Each exposed end of a stator pole tooth 7 and each pole shoe 15 is designed in  
3 such a fashion, for example, that a press fit is produced when joined. Any other  
4 type of mounting is feasible.

5  
6 A stator 1 is achieved as a result, the inner diameter of which has a maximum  
7 tolerance of 0.05 mm between opposite pole shoes 15.

8  
9 During assembly, the pole shoes 15 are placed on the stator pole teeth 7 and  
10 fixed sufficiently on the stator pole teeth 7 using a mandrel inserted in the  
11 direction of the centerline 2, and centered in relation to the centerline 2.

12  
13 Figure 2 shows a pole shoe 15.

14 The pole shoe 15 comprises a groove 18 on an exterior surface 17, by means of  
15 which it is pressed onto the exposed end of the stator pole tooth 7, so that a  
16 press fit is produced. Magnetically soft material—"SMC" or "SMS" material—can  
17 be used as the material for the pole shoe 15 that is easy to manufacture and  
18 shape using pressing technology.

19  
20 A stator according to the related art consists of stacks of individual laminations. It  
21 requires considerable expenditure to manufacture a laminated pole shoe out of  
22 individual laminations, however.

23  
24 An opening angle  $\alpha$  encompassing the length of the pole shoe 15 in the  
25 circumferential direction around the centerline 2 can therefore be enlarged  
26 compared with the related art, which makes a gap in the foot of the tooth 20  
27 (Figure 1) smaller in size, and a stop torque for a transition between two detent  
28 positions is therefore reduced, because magnetic resistance is reduced due to a  
29 smaller gap in the foot of the tooth 20.

30  
31 Figure 3 shows an oblong pole shoe 24.

1 The oblong pole shoe 24 is a pole shoe 15 that is longer in both axial directions  
2 than an exemplary embodiment according to Figure 2, the groove 18 of which  
3 oblong pole shoe 24 is closed on both ends by the extension and forms an  
4 indentation 26.

5  
6 Figure 4 shows an oblong pole shoe 24 on which the coil frame 28 is located.

7  
8 The coil frame 28 is integrally extruded on the oblong pole shoe 24 using plastic,  
9 for example. Undercuts, for example, are provided in the pole shoe 15 or the  
10 oblong pole shoe 24, i.e., a snap-in connection with the pole tooth 7 is formed, so  
11 that the coil frame 28 is fixed in position on the pole tooth 7.

12  
13 A coil 11 is wound on the coil frame 28 that can be inspected before installation  
14 on the stator ring 3, i.e., only inspected coils 11 are installed. Therefore, a stator  
15 1 that tests out poorly that comprises coils 11 wired together need not be thrown  
16 out entirely due to one bad coil 1.

17  
18 One part of the coil 11 (not shown) in a winding head space 23 is located on one  
19 axial end of the coil frame 28. The oblong pole shoe 24 makes it possible to  
20 direct a magnetic stray flux of an exciting coil 11 in defined fashion in the region  
21 of the winding head space 23 of the coil 11 as well, and therefore also  
22 contributes to the torque when a rotor is dimensioned accordingly.

23  
24 The coil frame 28 also provides electrical insulation for the coil 11 from the pole  
25 tooth 7 and/or the pole shoe 15 or the oblong pole shoe 24. The coil frame 28  
26 comprises at least one electrical connecting element 34 that serves to contact at  
27 least one end of a coil 11 with an external power supply. In this exemplary  
28 embodiment, the electrical connecting elements 34 are formed by two pins 38  
29 located in the coil frame 28. The electrical connecting element 34 can also be an  
30 insulation displacement connection.

31